

Xmat™ MG-150

Thin Heating Mats (c/w Single Cold Tail)

Devex Systems' NEW X mat MG-150 electric floor heating mat can be easily installed over existing tiles or into thin adhesive beds, thin screeds on concrete floors, levelling compounds and on fibre cement sheeting. The mat uses a twin conductor heating, cable with very low EMF, for ease of installation. The mat thickness of only 3.5 mm enables underfloor heating installations into most quality two-part adhesives with a minimal increase in floor height. This system is suitable for connection to a 'Continuous 24-hour' or 'Time of Use' tariff as a direct acting or background heating system. The mat comes with a single cold tail of 3 meters. The heating cable complies with IEC60800:2009.

We recommend the use of F-Board Insulation with electric floor heating to improve warm up times and reduce running costs.

- 20 year warranty
- Output power based on 230 volts
- Operating Temperature Range: -30°C to +80°C
- Minimum Temperature during Installation: -5°C



Xcable™ CK-17

In Screed Heating Cable (c/w Single Cold Tail)

Devex Systems' NEW X cable CK-17 electric floor heating screed cable is suitable for a wide range of indoor floor constructions and pipe tracing systems. It is a high performance, flexible cable made with quality fluoropolymer insulated conductors and a tough and durable PVC outer sheath. The cable is rated to 17 watts per meter and comes with a single cold tail of 3 meters. The heating cable complies with IEC60800:2009.

We recommend the use of insulation with electric floor heating to improve warm up times and reduce running costs.

- 20 year warranty
- Output power based on 230 volts
- Maximum Operating Temperature: +70°C



p: 1800 636 091 | e: info@devexsystems.com.au | w: www.devexsystems.com.au

Xcable™ CT-30

In Slab Electric Heating Cable (c/w Single Cold Tail)

Devex Systems' NEW X cable CT-30 electric floor heating cable can be installed into concrete slabs under a wide range of floor coverings and can also be used for snow melting applications. The CT-30 has a very low EMF and its single cold tail makes it easy to install. The CT-30 is most suited to be connected to an "Off-Peak" or "Time of Use" tariff as an in-slab storage heating system. The cable is rated to 30 watts per meter and it comes with a single 3 meter cold tail.

- 20 year warranty
- Output power based on 230 volts
- Maximum Operating Temperature: +70°C



Xthermostat™ TS Range

The X thermostat range of thermostats are specifically designed to work with the X cable and X mat range of products. They ensure simple and precise control of floor heating systems and other radiant heating systems like ceiling heating. There are over 6 different models to select from, all with sleek, modern designs and the latest technology including Wifi options.



Xboiler™ DB Range

The X boiler range of condensing gas boilers are modern, European made devices that offer a range of benefits to the home owner. Their advanced design and compact size make them suitable for a variety of different locations throughout the home. These systems have a very wide range of modulation that allow the boiler to heat very small areas with low heat demand. Their transparent control panels make these boilers very easy to use and they are adapted to work with domestic hot water tanks, solar systems, heat pumps and multi zone hydraulic separators.

